

HAND GESTURE TO VOICE CONVERSION AND HEALTH MONITORING SYSTEM

¹Himani Somisetty, ²Gaddam Vyshnavi, ³Pinapala Jyothirmayee, ⁴Alavala Jasmitha Reddy, ⁵Dasari Priyadarsini
¹⁻⁵UG Students, Department of Electronics and Communication Engineering
Vasireddy Venkatadri Institute of Technology, Andhra Pradesh, India

Abstract : Effective communication and continuous health monitoring play a crucial role in assistive technologies, especially for individuals with speech impairments. In this work, we developed a smart system that combines hand gesture recognition with real-time health monitoring using IoT. The system is implemented using a Raspberry Pi 3 Model B+ as the central processing unit. Hand gestures are captured using an MPU6050 sensor, which records motion and orientation data. These signals are processed to identify predefined gestures, which are then converted into voice output using a speaker. This enables users to communicate without verbal speech. Simultaneously, health parameters such as heart rate and SpO₂ levels are measured using the MAX30102 sensor. The collected data is transmitted to the ThingSpeak cloud platform, allowing caregivers to monitor the user's condition remotely. Experimental results show that the system performs reliably in both communication and health monitoring, making it suitable for practical assistive applications.

Keywords – Gesture Recognition, Raspberry Pi, ADC, IoT, Health Monitoring, Flex Sensor.

I. INTRODUCTION

Communication is essential for human interaction, as it allows individuals to express their needs and emotions. However, people with speech impairments often face difficulties in conveying information effectively. Although sign language is widely used, it is not universally understood, which creates communication barriers, particularly in emergency situations. To overcome these challenges, gesture-based communication systems have gained attention. These systems interpret hand movements and convert them into meaningful outputs such as text or speech. Compared to traditional methods, gesture recognition provides a more natural and user-friendly way of interaction.

In this project, we propose a wearable glove-based system that detects hand gestures using flex sensors. The analog signals from these sensors are converted into digital form using an ADC and processed by the Raspberry Pi. Based on predefined thresholds, gestures are classified and mapped to specific voice messages.

In addition to communication, the system also integrates health monitoring features. Parameters such as heart rate and oxygen levels are continuously measured, ensuring user safety. The integration of IoT enables remote monitoring, making the system more effective in real-world healthcare scenarios.

II. LITERATURE SURVEY

Several researchers have explored gesture recognition systems using different approaches. Earlier systems mainly relied on flex sensors and microcontrollers to detect hand movements and convert them into text outputs. While these systems were simple and cost-effective, they lacked processing efficiency and scalability.

Later, camera-based methods using image processing and machine learning techniques were introduced. These approaches improved accuracy but required high computational power and complex hardware, making them less suitable for portable applications.

In the field of healthcare, IoT-based monitoring systems have been widely developed to track vital parameters such as heart rate and oxygen levels. These systems provide real-time data and enable remote monitoring through cloud platforms. However, most existing systems focus on either gesture recognition or health monitoring independently.

Very few solutions combine both functionalities into a single system. In our work, we address this gap by integrating gesture-based communication with real-time health monitoring using a Raspberry Pi platform.

III. SYSTEM ARCHITECTURE

The overall system is designed using a modular approach to ensure efficient operation and easy implementation. It consists of input, processing, and output layers. At the input level, sensors such as flex sensors, MPU6050, and MAX30102 are used to collect gesture and health data. Since flex sensors produce analog signals, an ADC is used to convert them into digital values. The Raspberry Pi 3 Model B+ acts as the main processing unit. It receives data from all sensors and performs gesture recognition as well as health data analysis. The system is designed to handle multiple operations simultaneously. A priority mechanism is implemented to handle critical conditions. For example, if abnormal health values or fall detection is observed, the system immediately generates alerts through voice. The processed data is then transmitted to the cloud platform using wireless communication, enabling real-time monitoring.




FIG-1 : BLOCK DIAGRAM

IV. SYSTEM IMPLEMENTATION DETAILS

The implementation of the proposed system focuses on achieving a balance between performance and simplicity. The Raspberry Pi is programmed using Python, as it provides flexibility in handling sensor inputs and executing multiple processes simultaneously. Sensor communication is established using standard protocols such as I2C, which ensures reliable data transfer with minimal wiring complexity. The ADC module is used to interface analog sensors, allowing accurate digitization of input signals. The text-to-speech functionality is implemented using built-in audio libraries, enabling the system to produce clear voice output. The overall system is powered using a regulated power supply to maintain stable operation during continuous use. Care was taken to organize the hardware components in a compact manner so that the system can be easily worn or carried. This makes it suitable for real-time usage without causing discomfort to the user.




FIG-2 : CIRCUIT ARRANGEMENT

V. METHODOLOGY

The system operation begins with the detection of hand gestures using flex sensors placed on a glove. These sensors produce varying signals depending on finger movement. The analog signals are converted into digital form using an ADC. The Raspberry Pi processes this data and compares it with predefined threshold values to identify specific gestures. Once a gesture is recognized, it is mapped to a corresponding message. This message is then converted into speech using a text-to-speech module and played through a speaker. At the same time, the message is displayed on a screen. In parallel, the system continuously monitors health parameters such as heart rate and SpO₂ levels using the MAX30102 sensor. The MPU6050 sensor is used to detect motion and fall conditions. All the collected data is analyzed in real time. If any abnormal condition is detected, the system triggers an alert through voice. The data is then sent to the ThingSpeak cloud platform for remote monitoring.

VI. DATA PROCESSING AND DECISION LOGIC

To ensure reliable gesture recognition, the raw sensor data is first stabilized using basic filtering techniques. Small fluctuations in sensor values are minimized by averaging multiple readings over a short time interval. This helps in reducing noise caused by unintended hand movements. After filtering, the processed values are compared against predefined ranges assigned to each gesture. Instead of relying on a single reading, the system checks for consistency over a sequence of values before confirming a gesture. This approach improves accuracy and avoids false detection. For health monitoring, threshold limits are defined for parameters such as heart rate and oxygen levels. If the measured values exceed or fall below the normal range, the system identifies it as an abnormal condition. In such cases, priority is given to health alerts over gesture output to ensure user safety.

VII. RESULTS AND DISCUSSION

The system was tested under various conditions to evaluate its performance. The gesture recognition module successfully identified most predefined gestures with good accuracy. The response time was observed to be quick, allowing real-time communication. The voice output generated by the system was clear and understandable. The use of motion sensing helped reduce errors caused by unintended hand movements. In terms of health monitoring, the system provided stable and reliable readings for heart rate and oxygen levels. Fall detection was also successfully implemented using motion data. The data transmission to the cloud platform was smooth, enabling real-time updates. Alerts were generated correctly during abnormal conditions, ensuring timely response. The system achieved an approximate gesture recognition accuracy of 90–95%, with an average response time of 1–2 seconds under normal operating conditions.



FIG-3 : OUTPUT OF HEARTBEAT AND SPO2 IN THINGVIEW APP




FIG-4 : OUTPUT OF TEMPERATURE AND FALL STATE IN THINGVIEW APP

Performance Evaluation : To evaluate the effectiveness of the system, multiple test cases were conducted with different users and gesture patterns. It was observed that the system performs consistently when the gestures are clearly defined and executed within the expected range. The average response time between gesture input and voice output was found to be minimal, making the system suitable for real-time communication. Minor delays were only noticed when multiple processes were executed simultaneously, but they did not significantly affect overall performance. In health monitoring, the sensor readings were compared with standard measurement devices, and the variation was found to be within acceptable limits. This indicates that the system can provide reasonably accurate health data for basic monitoring purposes. The reliability of cloud communication was also tested under different network conditions. Even with moderate connectivity, the system was able to transmit data successfully, although slight delays were observed in some cases.

VIII. ADVANTAGES OF THE PROPOSED SYSTEM

The proposed system offers several advantages compared to existing solutions. One of the main benefits is the integration of communication and health monitoring into a single platform, reducing the need for multiple devices. The system is designed using easily available components, which keeps the overall cost low. This makes it accessible for a wider range of users, especially in resource-limited settings. Another advantage is the real-time operation, which allows immediate response in both communication and emergency situations. The use of IoT further enhances the system by enabling remote monitoring. The compact design and simple user interface make the system easy to use, even for individuals with limited technical knowledge.

IX. CONCLUSION

In this work, we developed a smart assistive system that integrates gesture-based communication with real-time health monitoring. The system enables users to communicate through simple hand gestures, improving accessibility for individuals with speech impairments. The inclusion of IoT allows continuous monitoring of vital health parameters and remote access to data. This enhances patient safety and enables quick response during emergencies. The system is compact, cost-effective, and easy to use, making it suitable for real-world applications. Future improvements can focus on increasing gesture accuracy using machine learning and expanding the system for multilingual support.

X. FUTURESCOPE

The current system can be further improved by incorporating machine learning techniques for gesture recognition. This would allow the system to adapt to different users and improve accuracy over time.

Additional health parameters such as body temperature and blood pressure can be included to make the system more comprehensive. Integration with mobile applications can also enhance accessibility and user interaction.

Another possible improvement is the use of wireless wearable sensors to reduce hardware complexity and improve comfort. The system can also be extended to support multiple languages, making it more useful in diverse environments.

REFERENCES

- [1] T. Hobbs and A. Ali, Smart Home Control Using Real-Time Hand Gesture Recognition and Artificial Intelligence on Raspberry Pi, *Electronics Journal*, 2025
- [2] Gautham Krishna G et al., A Generic Multi-modal Dynamic Gesture Recognition System using Machine Learning, *arXiv*, 2018.
- [3] Thomas Stadelmayer et al., Light-weight Gesture Sensing Using FMCW Radar Time Series Data, *arXiv*, 2021.
- [4] Mr.P.V.KrishnaRao,V.Niharika,V.Prashanthi,V.Akhila,V. Gayathri “Hand Gesture Recognition and Voice Conversion System for Dumb and Deaf People”-Journal of Emerging Technologies and Innovative Research (JETIR) Journal-Volume:6,Issue:4,2019
- [5] Yuvraj Grover; Riya Aggarwal; Deepak Sharma; Prashant K. Gupta “Sign Language Translation systems for hearing/speech Impaired People: Review”- ICIPTM-2021
- [6] S. Vigneshwaran, M. Shifa Fathima, V. Vijay Sagar, R. Sree Arshika “Hand Gesture and Voice Conversion System for Dumb People”-ICACCS- 2019
- [7] Boon Giin Lee, Su Min Lee” Smart Wearable Hand Device for Sign Language Interpretation System With Sensors Fusion”- IEEE Sensors Journal -Volume: 18, Issue:3, Feb.1, 1 2018
- [8] K Abhijith Bhaskaran;Anoop G. Nair;K Deepak Ram; Krishnan Ananthanarayanan; H.R. Nandi Vardhan “ Smart gloves for hand gesture recognition: Sign language to speech conversion system”-RAHA-2016